

MACINA KAPOHO

273 11 PT-CX5I

1x11

SHIMANO
XT



27.5"/29"

Dimmix

160mm



16 17 19 21
41 43 48 53
cm



BIKE CATEGORY

E4



TAPERED
STEERER



GRAVITY
CASTING



INTERNAL
CABLE ROUTING



HYDRO
FORM

MOTOR BOSCH DRIVE UNIT 36V-250W, 25km/h
PERFORMANCELINE CX

BATTERY Powertube 13.4Ah - 500Wh

DISPLAY Intuvia LCD Display,
Remote w/Walkassist

ITEM NO. 798407xxx

COLOUR Black matt (toxicgreen)

FRAME Macina Kapoho 27.5"+, Alloy
4-linkage POP System - LT 160mm, boost 148mm
Battery full-Integrated

SHOCK RockShox Monarch RL

FORK Suntour Aion 35. air, LOR, T-15x110

BRAKE Shimano Deore XT M8000 / Rotor 203-180

SHIFTLEVER Shimano Deore XT M8000-11

R. DERAILLEUR Shimano Deore XT M8000 GS shadow +

SPROCKET Shimano M7000-1111-46, DT H1900 Hybrid F: 29"

WHEELSET R: 27.5" plus B/B Tubeless

DT Swiss straightpull - Boost 110/148

TIRE F: Schwalbe Fat Albert, snakeskin, Addix, 60-622,

R: Schwalbe Nobby Nic, snakeskin, Addix, 70-584

SEATPOST KTM Comp, JD-YSP22L adjustable,

extern vers, w/Rem

WEIGHT 24,0 kg with pedal

GEOS



	Size in cm / inch	Top tube length	Seat angle	Head angle	Head tube length	Chainstay length	Wheelbase	Stack	Reach	Standover height	BB drop
41	16	565	74,5°	66,0°	120	498	1201	629	388	818	12
43	17	585	74,5°	66,0°	120	498	1221	643	402	813	12
48	19	605	74,5°	66,0°	125	498	1242	634	425	841	12
53	21	625	74,5°	66,0°	137	498	1263	645	442	869	12

MACINA KAPOHO
271. 272. 273