

# MACINA KAPOHO

274 11 PT-CX5I

1 x 11

SHIMANO  
SLX

27.5+

160mm

16 17 19 21  
41 43 48 53  
cm

BIKE CATEGORY  
E4



TAPERED  
STEERER



GRAVITY  
CASTING



INTERNAL  
CABLE ROUTING



HYDRO  
FORM

**MOTOR** BOSCH DRIVE UNIT 36V-250W, 25km/h  
PERFORMANCELINE CX

**BATTERY** Powertube 13.4Ah - 500Wh

**DISPLAY** Intuvia LCD Display,  
Remote w/Walkassist

**ITEM NO.** 798408xxx

**COLOUR** Black matt (white glossy)

**FRAME** Macina Kapoho 27.5"+, Alloy

4-linkage POP System -

LT 160mm, boost 148mm

Battery full-integrated

**SHOCK** RockShox Monarch RL

**FORK** Suntour Zeron35 coil, LOR, T-15x110

**BRAKE** Shimano M6000 / Rotor 203-180

**SHIFTLEVER** Shimano SLX M7000-11

**R. DERAILLEUR** Shimano SLX M7000 GS shadow +

**SPROCKET** Shimano M7000-1111-46

**WHEELSET** KTM Line 27.5+ B/B

Ryde Edge 35 / Shimano Deore - Boost 110/148

**TIRE** Schwalbe Nobby Nic, Perf. -folding - 70-584

**SEATPOST** KTM Comp, JD-YSP22L adjustable,  
extern vers. w/Rem

**WEIGHT** 24,5 kg with pedal

## GEOS



	Size in cm / inch	Top tube length	Seat angle	Head angle	Head tube length	Chainstay length	Wheelbase	Stack	Reach	Standover height	BB drop
41	16	565	74,5°	66,5°	120	498	1201	639	388	814	12
43	17	585	74,5°	66,5°	120	498	1221	639	408	808	12
48	19	605	74,5°	66,5°	125	498	1242	644	426	836	12
53	21	625	74,5°	66,5°	137	498	1263	655	443	864	12

MACINA KAPOHO  
274