

# MACINA FUN

9 SI-P5I



1x9

SHIMANO  
DEORE

 46 51 56 60  
cm

 46 51 56  
cm

 46 51 56  
cm



BIKE CATEGORY

E2

**MOTOR** BOSCH DRIVE UNIT 36V-250W, 25km/h  
PERFORMANCELINE

**BATTERY** Powerpack 13.4Ah - 500Wh

**DISPLAY** Intuvia LCD Display,  
Remote w/Walkassist

**ITEM NO.** 798458xxx

**COLOUR** Black matt (orange+white)

**FRAME** Macina Trekking Onroad Alloy, Trekking.Disc  
Battery semi-integrated

**FORK** Suntour NEX E25 coil, HLO (SF15)

**BRAKE** Shimano M365 / Rotor 180-160

**SHIFTLEVER** Shimano Alivio M4000-9

**R. DERAILLEUR** Shimano Deore M592 SGS-shadow

**SPROCKET** Shimano HG201-9 silver 11-36

**WHEELSET** KTM Line 700C, Ambrosio / Shimano Deore

**TIRE** Schwalbe Energizer plus 40-622




**SADDLE** Selle Royal Look-In Moderate

**SEATPOST** KTM Line Satori Elegance LT 30.9/300

KTM Line 006 Hinterbauständer

**KICKSTAND** KTM Racktime E-Bike Universal

**CARRIER** B+M Lumotec IQ-Avy E, LED-40 Lux, 6VDC

**LAMP F**   24,6 kg  25,0 kg

**WEIGHT** with pedal and kickstand

## GEOS



Size in  
cm / inch

Top tube  
length

Seat angle

Head angle

Head tube  
length

Chainstay  
length

Wheelbase

Stack

Reach

Standover  
height

BB drop

MACINA SPORT XT 11 CX5+,  
XT 11 CX5, 11 CX5, 10 CX5,  
9 CX5 / STYLE XT11 CX5,  
10 CX5 / TOUR 10 PS / FUN 9 PS /  
GRAN 8 PS **MAN** MACINA FLITE 11  
CX5, STREET 11 CX5

46 18	575	73,0°	71,0°	120	463	1082	584	396	777	55
51 20	588	73,0°	71,0°	137	463	1096	601	405	808	55
56 22	599	73,0°	71,0°	155	463	1108	618	411	840	55
60 23,5	615	73,0°	71,0°	174	463	1125	636	422	869	55

MACINA SPORT XT 11 CX5+,  
XT 11 CX5, 11 CX5, 10 CX5,  
9 CX5 / STYLE XT11 CX5,  
10 CX5 / TOUR 10 PS /  
FUN 9 PS / GRAN 8 PS **LADY**

46 18	575	73,0°	71,0°	120	463	1082	584	396	708	55
51 20	588	73,0°	71,0°	137	463	1096	601	405	710	55
56 22	599	73,0°	71,0°	155	463	1108	618	411	741	55

MACINA SPORT 10 CX5, 9 CX5 /  
10 PS / FUN 9 PS / EIGHT XL PS,  
RT A5 / CITY 8 PS, RT A5, A4,  
RT A4 US

46 18	595	71,0°	70,0°	160	492	1104	625	382	435	60
51 20	605	71,0°	70,0°	174	492	1123	639	387	435	60
56 22	621	71,0°	70,0°	190	492	1132	653	400	435	60